



### Features

- Versatile and Adaptable
- Fast Print Speed at 250mm/s
- Easy Paper Loading for Paper Replacement
- Support Graphics and Barcode Printing
- Complete Compatibility with EPSON & SAMSUNG



### Specifications

Model	SP-POS88IV-S	SP-POS88IV-P	SP-POS88IV-U
Interface Type	RS-232	LPT	USB
Print	Printing Method	Thermal Line	
	Printing Speed	250mm/s	
	Resolution	8 dots/mm, 576 dots/line	
	Effective Printing Width	72mm	
Character	Character Set	ANK, GB18030(Chinese)	
	Print Font	ANK: 12 x 24 Chinese: 24 x 24	
	Character per Line	42	
Paper Spec	Paper Type	Thermal paper	
	Paper Width	79.5± 0.5mm	
	Paper Roll Diameter	Max: 80.0mm	
	Roll Core Inner Diameter	13mm(min.)	
	Paper Thickness	0.06 to 0.07mm	
Paper Supply Method	Drop-in paper load		
Reliability	MCBF	60 million lines	
	TPH	100km	
	Auto Cutter	500,000 cuts	
Barcode Types	UPC-A, UPC-C, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93, CODE128		
Emulation	ESC/POS		
Sensor	Paper Near End Sensor, Paper End Sensor		
Drawer Port	1 Port		
Power Supply (Adapter)	AC100 ~240V ± 10%(include) DC 24V, 2A		
Auto Cutter	Type	Guillotine	
	Life	500,000 Cuts	
	Cutting Method	Full / Partial Cut	
Net / Gross Weight	1.63 / 2.90kg		
Printer Dimension	150 x 192x 150 mm (W x L x H)		
<i>In the interest of improvement, specifications may change prior to notice</i>			